

用途 Purposes			SP-1310AS/2210AS - 		
H	厚料 Heavy Material		M	中厚料 Medium Heavy Material	
			X	极厚料 Super-heavy Material	

压脚驱动方式 Presser foot drive					
S	压脚电磁式驱动 Solenoid-driven			压脚气动式驱动 Pneumatic driven	

规格	Specification
----	---------------

型号 Model	 平缝 Flat Seam	 2倍摆梭 2-time shuttle hook	 缝纫面积 Sewing area	 针距 Needle Length	 切线装置 Cutting device	 扫线装置 Scavenging device	 最高缝纫速度 Highest sewing speed	 气压 Air pressure
SP-1310AS	★	★	130 × 100mm	0.05 – 12.7mm	★	★	2,800 rpm	1.8 L/min
SP-2210AS	★	★	220 × 100mm	0.05 – 12.7mm	★	★	2,800 rpm	1.8 L/min

型号Model	SP-1310AS/BS		SP-2210AS/BS	
	HS/MS	H/M/X	HS/MS	H/M/X
线迹Line	单针平缝Single-needle flat seam			
最高缝纫速度Highest sewing speed	2,800 rpm			
缝制区域(X×Y) Sewing area	130×100 mm		200×100 mm	
送布装置 Cloth feeding device	间歇送布（脉冲马达驱动）Intermittent feeding (driven by pulse motor)			
针距Stitch length	0.05 - 12.7mm			
最大针数 Max. needle number	20,000针/1个图案(20,000 needles/1 pattern)			
压脚驱动方式 Foot presser driving mode	脉冲马达驱动 Pulse motor drive	气动 Pneumatic	脉冲马达驱动 Pulse motor drive	气动 Pneumatic
压脚高度 Work Clamp Height	HS/MS:最大25 mm-0 H/M/X:最大30 mm maximum 25 mm maximum 30 mm			
两步压脚 2-step presser foot	一体式压脚 All-in-one presserfoot	分离式压脚 Divided presser foot	一体式压脚 All-in-one presserfoot	分离式压脚 Divided presser foot
间歇压脚上升量 Rising amount of intermittent foot presser	22 mm			
间歇压脚行程 Stroke by intermittent presser foot	0或2 - 10 mm（出厂设置：3mm） 0 or 2 - 10 mm（Factory defaults: 3mm）			
旋梭 Hook	两倍摆梭 Double Shuttle Hook			
扫线装置 Thread Wiper	标准装备 /Standard facility			
切线装置Cutting device	标准装备 /Standard facility			
数据存储方式Data storage way	USB			
马达 Motor	AC伺服马达550W /AC servomotor 550W			
机器尺寸 Machine size	1200×895×1250		1200×900×1300	
包装尺寸Packing size	1300×1000×1350		1400×1000×1400	
重量Weight	170kg		170kg	
电源Power	单相Single phase 220V, 3相 3-phase 380V			
气压Air pressure	0.5 Mpa 1.8 L/min			

以上型号仅供参考，详细情况请咨询当地经销商。
The above types are only for reference, and you can consult local distributors for details.

为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.

舒普智能技术股份有限公司
SUPREME INTELLIGENT TECHNOLOGY CO.,LTD

地址：宁波市鄞州区金谷北路219号
No. 219 North Jingu Rd. Yinzhou District, Ningbo
315100, China

TEL: 0086-574-88393716 88393738
FAX: 0086-574-88393717
E-mail: china-supreme@vip.163.com

www.china-supreme.com

为时尚产业 提供智能制造解决方案

*Intelligent manufacturing
Solutions for fashion industries*

SP-1310AS-HS/MS

SP-1310AS-H/M/X

SP-2210AS-H/M/X

SP-2212BS-H/M/X

电子花样机
Electronic Pattern Sewing Machine



SP系列电子花样机，高效美观的缝制效果，缝制范围更广，适用性更强，使用节能技术，机器更节能环保。
主要应用于服装行业的各种男女装、牛仔布、针织物，女士内衣、箱包、鞋类等各种不同用途。

SP series electronic pattern sewing machine with fastest speed, efficient and beautiful sewing line, wider sewing range, stronger applicability, using energy-saving technology, it is more environmental friendly, mainly used in all kinds of men and women apparel industry, denim, knits, intimates, luggage, footwear and other purposes.



SUPREME
创新 · 智造
Innovation & Creation

性能优势

Characters

- 张力一致的缝制
 - 高品质缝纫
 - 断线感应器
 - 耗电低、高转速、高效能
- 花样编辑快速简便
 - 强化机针贯穿力
 - 优越的扩展改装空间
 - 触摸屏内置两种编辑软件
 - 电子夹线功能
- Substantial tension
 - Quality stitching
 - Thread breakage detector
 - Low power consumption, high speed, high efficiency
- Editable pattern
 - Strong penetration needle
 - Extended output
 - Two types of editing softwares.
 - Electronic thread clamping function.

产品特点

Product features

- USB接口为标准配置，通过使用U盘或读卡器，可实现对各种记忆体（FD，SM，CF，SD等）进行数据的导入及导出。
 - 兼容210D、210E及PLK系列花样机BA花样
 - 强大的数据兼容性可极大的减少输入花样的重复劳动
 - 由于采用了舒普公司的电脑直驱式马达，启动/停车反应迅速、平稳，与传统机型相对比机器运行时间缩短了约19%，生产效率得到进一步提高。
- The machine is equipped with standard slot of USB port. By using USB disc or card reader, it can achieve the data input and output for various storage devices.
 - Machine is Compatible with the patterns of 210D, 210E and PLK patterns sewing machine series.
 - Powerful data compatibility can greatly reduce the repeated labor of inputting program.
 - Due to the adoption of the direct drive computer motor of Supreme company, the start/stop response is rapid and smooth, and the running time of the machine is reduced about 19% comparing with the traditional model, and the production efficiency is further improved.


侧滑压脚花样机

Sliding Pattern Tacker Machine

SP-1310AS-H/CH

130×100mm

- 专门针对特殊缝纫的面料而设计，广泛应用于服装贴标、箱包图案的缝纫；
Sliding pattern tacker machine is especially designed for clothes labels and bag patterns.



在缝纫过程中压脚可根据客户编辑的花样侧面滑动，确保面料在缝纫过程中不会移位，省去了传统工艺中的诸多中间环节，省时，高效。缝制的有效范围在130mm×100mm；此款侧滑压脚装置可以根据用户需求安装到SP-2210AS-H机型上。

To prevent the material from moving while sewing, the sliding device slides to fix the material designed, which saves steps adopted in traditional sewing. This machine, with a sewing area 130mm×100mm, saves energy and improves efficiency greatly. This special device is also compatible with SP-2210AS-H.


翻转压脚花样机

Flip Flop Pattern Tacker Machine

SP-1310AS-H/FZ

130×100mm

- 专门针对特殊缝纫的面料而设计，主要应用于各种不同规格尺寸的标牌缝纫；
This machine, especially designed for special fabric, was mainly adopted in label attaching with varied size.



通过专业的压脚和模板制作，非常精确的缝制各种标牌，缝制范围是130mm×100mm。此款翻转压脚装置也可以根据用户的需求安装到SP-2210AS-H机型上。

By professional foot presser and model plate produced by supreme, this machine accurately sews various labels with sewing size 130mm×100mm. The flip flop device is also compatible with SP-2210AS-H machine.

热切安全带机

Hot Cut Safe Belt

SP-1310AS-X/RQ

130×100mm

- 专业用于缝制安全带；
Special designed for various size of safe belt.



切线装置是热切，以免安全带的缝纫线被切刀剪断后全松散，可以避免脱线或勾不上线等缺陷，安全带所缝制的有效范围在130mm-100mm□此款热切安全带装置也可以根据用户需求安装到SP-2210AS-H机型上。

CSM-1310G-01A/RQ pattern tacker machines with hot cutting device is used to sew different sizes safety belts. The thread hot cutting device can avoid the thread tail to be loosen and released after hot cutting and guarantee the cutting nice and firm. The sewing size is 130-100mm; and also it can be fixed on CSM-2210GB-01A by request.