

SP-F136

贴底档机

Reinforcement tape machine



性能优势

操作方式简单，员工只需将一卷带子放在料架上，按下启动键，机器安照尺寸自动裁好带子，自动折叠两端，自动送料，将裤子缝纫部位放机器缝纫区域踩下脚踏即可。对操作人员无需特别的技术要求，精确的折料方式确保带子长度一致，缝纫整齐牢固。带子尺寸可根据客户需求进行调节。

Advantages

The operation method is simple, the employee only needs to put a roll of tape on the material rack, press the start button, the machine will automatically cut the tape according to the size, automatically fold the two ends, automatically feed the material, put the sewing part of the trousers in the sewing area of the machine and step on the foot pedal. No special technical requirements are required for the operator, and the precise folding method ensures that the length of the belt is consistent and the sewing is neat and firm. The strap size can be adjusted according to customer needs.

效率

自动切料、折料、送料、车缝一次性自动完成。做1个裤档加固只需要10秒。

Efficiency


Automatic cutting, folding, feeding and sewing are automatically completed at one time. It only takes 10 seconds to do a trouser reinforcement.

适用范围

主要用于加固裤子档部及类似工艺

Application

Mainly used for reinforcement of trousers and similar processes



视频及资料下载
Video and data download

最高缝纫速度 Highest sewing speed	2700rpm	气压 Air pressure	0.5Mpa,1.8L/min
线迹 Stitch	单针平缝 Single needle lockstitch sewing	重量 Weight	250Kg
使用料宽 Using the material width	30-70mm	外型尺寸 Dimensions	1200×720×1220mm(L×W×H)
电压 Voltage	单相 Single phase 220V		

以上基础参数表为标准款机型