

多针杆电子花样机

Multi needles electronic pattern sewing machine

SP-2210AS-H/DN 双针杆

SP-3020AS-H/DN 双针杆

SP-6040AS-H/DN双针杆

SP-6040AS-H/TN三针杆



H 厚料的缝纫
Heavy Material

M 中厚料的缝纫
Medium Heavy Material

X 极厚料的缝纫
Super-heavy Material



视频及资料下载
Video and data download

性能优势

该双针杆机构可以舒普多款机型使用，只要选择一款适合您的机型，能够切实感受到双针缝纫机带来的高生产效率体验。

注：选购功能装置：二次夹线装置、自动绕线换梭装置

Advantages

The double needle mechanism can be used in various models of Supreme. You can choose a model requested and use double needle version, it will help you to improve the efficiency.

Note: Optional device: secondary thread clamping device, automatic winding & shuttle changer

规格 Specification

型号 Model	SP-2210AS-H/DN		SP-3020AS-H/DN	SP-6040AS-H/DN	SP-6040AS-H/TN
名称 Name	多针杆电子花样机Multi needles electronic pattern sewing machine				
线迹Line	单针平缝 / Sing-needle flat seam				
最高缝纫速度Highest sewing speed	2,800 rpm				
缝制区域Sewing area device	220×100 mm	300×200 mm		600×400 mm	600×400 mm
送布方式Cloth feeding mode	间歇送布 (脉冲马达驱动) Intermittent feeding (driven by pulse motor)			间歇送布 (伺服马达驱动方式) / Intermittent feeding (Servo motor drive mode)	
针距长度Stitch length	0.05-12.7mm				
最大针数Max. needles number	20,000针/1个图案 / 20,000 needles/1 pattern				
可储存针数Maximum storage of stitch	内置内存可存储500000针/Maximum 500000stitch in inner storage				
压脚驱动方式Presser foot device	气动/Pneumatic				
压脚高度Work clamp height	最大Max. 30mm				
两步压脚2- step presser foot	一体式压脚/All-in-one presser foot				
大压脚高度Big foot presser height	最大/Max. 30mm				
大压脚形式Big foot presser method	一体式压脚/All-in-one presser foot				
间歇压脚上升量Rising amount of intermittent foot presser	22mm				
间歇压脚上行程 Stroke by intermittent presser foot	0或2-10mm (出厂设置: 3mm) 0 or 2-10mm (Factory defaults: 3mm)				
扫线装置Thread Wiper	标准装备 / Standard facility				
切线装置Cutting device	标准装备 / Standard facility				
机器尺寸Machine size	1200×900×1230	1200×1200×1250		1400×1650×1400	1400×1800×1400
包装尺寸Packing size	1300×1000×1350	1300×1300×1400		1500×1800×1500	1500×1900×1500
重量Weight	170Kg	240Kg		330Kg	350Kg
马达Motor	AC伺服马达550W直接驱动式/AC servomotor 550W				
电源Power	单相Single phase200~240V, 3相3-phase 380V				
气压Air pressure	0.5Mpa、1.8L/min				

以上型号仅供参考，详细情况请咨询当地经销商。
The above types are only for reference, and you can consult local distributors for details.

为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.