

电子花样机

Electronic Pattern Sewing Machine

SP-4530BS-H/M/X

SP-6030AS-H/M/X

SP-6030BS-H/M/X

SP-6040AS-H/M/X

SP-6055BS-H/M/X

SP-10040BS-H/M/X



H 厚料的缝纫
Heavy Material

M 中厚料的缝纫
Medium Heavy Material

X 极厚料的缝纫
Super-heavy Material



视频及资料下载
Video and data download

性能优势

- 提高缝制品质
- 标配压脚装置
- 面线夹持装置
- 电子夹线器
- 耗电低、高转速、高效能

Performance advantage

- Improve sewing quality
- Standard presser foot device
- Needle thread holding device
- Electronic thread holding device
- Low power consumption, high speed, high efficiency

注：选购功能装置：二次夹线装置、自动换梭装置 Note: Optional device: secondary thread clamping device, automatic shuttle changer

规格 Specification

型号 Model	SP-6030AS	SP-6040AS	SP-4530BS	SP-6030BS	SP-6055BS
名称 Name	H/M/X 电子花样机 Electronic Pattern Sewing Machine				
线迹 Line	单针平缝 / Sing-needle flat seam				
最高缝纫速度 Highest sewing speed	2,800 rpm				
缝制区域 Sewing area device	600×300 mm	600×400 mm	450×300 mm	600×300 mm	600×550 mm
送布方式 Cloth feeding mode	间歇送布 (脉冲马达驱动) Intermittent feeding (driven by pulse motor)		间歇送布 (伺服马达驱动方式) / Intermittent feeding (Servo motor drive mode)		
针距长度 Stitch length	0.05-12.7mm				
最大针数 Max. needles number	20,000针/1个图案 / 20,000 needles/1 pattern				
可储存针数 Maximum storage of stitch	内置内存可存储500000针 / Maximum 500000stitch in inner storage				
压脚驱动方式 Presser foot device	气动 / Pneumatic				
压脚高度 Work clamp height	最大 Max. 30mm				
两步压脚 2-step presser foot	一体式压脚 / All-in-one presser foot				
大压脚高度 Big foot presser height	最大 / Max. 30mm				
大压脚形式 Big foot presser method	一体式压脚 / All-in-one presser foot				
间歇压脚上升量 Rising amount of intermittent foot presser	22mm				
间歇压脚上行程 Stroke by intermittent presser foot	0或2-10mm (出厂设置: 3mm) 0 or 2-10mm (Factory defaults: 3mm)				
扫线装置 Thread Wiper	标准装备 / Standard facility				
切线装置 Cutting device	标准装备 / Standard facility				
机器尺寸 Machine size	1400×1650×1400	1400×1650×1400	1200×1100×1400	1635×1300×1385	1400×1800×1400
包装尺寸 Packing size	1500×1800×1500	1500×1800×1500	1300×1200×1500	1750×1400×1500	1500×1900×1500
重量 Weight	330Kg	330Kg	300Kg	320Kg	350Kg
马达 Motor	AC伺服马达550W直接驱动式 / AC servomotor 550W				
电源 Power	单相 Single phase 200~240V, 3相 3-phase 380V				
气压 Air pressure	0.5Mpa, 1.8L/min				

以上型号仅供参考，详细情况请咨询当地经销商。
The above types are only for reference, and you can consult local distributors for details.

为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.