

# 为时尚产业 提供智能制造解决方案

*Intelligent manufacturing  
Solutions for fashion industries*

## SP-6040AS-H/M/X

电子花样机

Electronic Pattern Sewing Machine

H 厚料的缝纫  
Heavy Material

M 中厚料的缝纫  
Medium Heavy Material

X 极厚料的缝纫  
Super-heavy Material



- 伺服驱动  
X, Y采用伺服驱动, 使线迹更美观, 低噪音、低振动。
- 断线感应  
用于感应断线, 检测到断线时缝纫操作将自动停止。



- Servo motor drive  
Better stitch lines, lower noise and lower vibration generated by servo motor in X, Y direction.
- Thread-broken detector  
Used to detect broken-thread, which stops the machine as soon as it detects broken line.

主要应用于安全气囊、箱包等大范围缝制；多个小部件大范围组合缝制也是理想的选择。

Mainly used for big size materials like air bag and bags or for the big area sewing of combined small parts.



**SUPREME**  
创新 · 智造  
Innovation & Creation

## 客户体验 Customer experience



采用国际先进的驱动马达和双导轨，速度快振动小，生产性和舒适性双重保障。

Using leading technology parts as drive motor and dual-rail, the machine sews quickly with little vibration, which ensures productivity and comfort.

600×400mm的超大缝制范围，箱包/安全气囊/服饰等的大花样极佳选择

Best choice for big pattern material as bags/air bags /clothes with a sewing area 600×400mm

集合了舒普最先进的技术和客户的使用习惯，真正实现了超高精度超大范围的完美体验。

Considering cutting edge technology of Supreme and using habit of customers, this machine realizes best using experience with highest accuracy and big area.

配备了断线感应器，结合新一代操作软件，实现了自动感应自动停止自动报警多重功能，智能更节能。

Equipped with broken thread detector, this machine is able to stop and alert automatically using new operating software.

## 规格 Specification

型号 Model	平缝 Flat Seam	2倍旋梭 2-time hook	缝纫面积 Sewing area	针距 Stitch length	切线装置 Cutting device	扫线装置 Scavenging device	最高缝纫速度 Highest sewing speed	气压 Air pressure
SP-6040AS	★	★	600×400mm	0.05-12.7mm	★	★	2,800 rpm	1.8 L/min

型号 Model	SP-6040AS
	H/M/X
线迹Line	单针平缝 /Sing-needle flat seam
最高缝纫速度Highest sewing speed	2,800 rpm
缝制区域Sewing area device	600×400 mm
送布方式Cloth feeding mode	间歇送布(脉冲马达驱动) Intermittent feeding (driven by pulse motor)
针距长度Stitch length	0.05-12.7mm
最大针数Max. needles number	20,000针/1个图案 /20,000 needles/1 pattern
可储存针数 Maximum storage of stitch	内置内存可存储500000针/Maximum 500000stitch in inner storage
压脚驱动方式 Presser foot device	气动/Pneumatic
压脚高度Work clamp height	最大Max. 30mm
两步压脚2- step presser foot	一体式压脚/All-in-one presser foot
大压脚高度Big foot presser height	最大/Max. 30mm
大压脚形式Big foot presser method	一体式压脚/All-in-one presser foot
间歇压脚上升量Rising amount of intermittent foot presser	22mm
间歇压脚上行程Stroke by intermittent presser foot	0或2-10mm (出厂设置: 3mm) 0 or 2-10mm (Factory defaults: 3mm)
扫线装置 Thread Wiper	标准装备 / Standard facility
切线装置 Cutting device	标准装备 / Standard facility
机器尺寸 Machine size	1400×1650×1400
包装尺寸 Packing size	1500×1800×1500
重量Weight	330kg
马达Motor	AC伺服马达550W直接驱动式/AC servomotor 550W
电源Power	单相Single phase200~240V
气压Air pressure	0.5Mpa、1.8L/min

以上型号仅供参考，详细情况请咨询当地经销商。

The above types are only for reference, and you can consult local distributors for details.

为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。

Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.