

SP-S608-M / SP-C608-M

智能模板机

Intelligent template machine



性能优势

采用智能闭环缝制系统，实时监控缝制状态，以反馈交互的方式，调控缝制系统。
采用RFID先进芯片识别技术，反应更加快速、灵敏和准确。
采用首创重力式旋梭供油机构，从更根本上，保证供油力恒定，保证供油的稳定性。
采用大行程针杆机构，机针高度达22mm，在不同厚度的模板或布料的缝制，应用上，适用性更广泛。
采用智能机械压脚，在具备了智能控制系统的灵活性，同时也具备了机械结构稳定性。
采用丝杠传动系统，结合闭环电机，缝制精度达0.1毫米级别。
选购功能装置：激光切割、振动刀切割、自动换梭、丝杆模组、自动起缝装置

效率

通过智能缝制控制系统，特别适合花样复杂、线迹高标准要求的缝制作业。

适用范围

适用于服饰上拉链、工装前片等工艺，配备模板进行缝制作业。

Advantages



The intelligent closed-loop sewing system is adopted to monitor sewing operation in real time and to control the sewing operation by means of feedback interaction.
RFID advanced chip identification technology, easy to use, more rapid and accurate response.
Using gravity-type rotary hook oil supply technology, which ensures the constant oil supply and the stability.
Large stroke needle rod mechanism, needle height up to 22mm, enable to use for different thickness of fabrics and for different sewing application.
The intelligent mechanical presser foot has the flexibility of an intelligent control system and the stability of the mechanical structure.
Using screw rod with motor control, sewing accuracy can reach to 0.1 mm.
Optional: laser cutting, vibration knife cutting, double screw rods, automatic sewing function

Efficiency

Through the intelligent sewing control system, it is especially suitable for sewing industry with complex patterns and high stitch requirements.

Application

It is suitable for pocket welting, trousers placket etc. and combine with various templates.



视频及资料下载
Video and data download

最高缝纫速度 Highest sewing speed	3500rpm	气压 Air pressure	0.5Mpa、1.8L/min
缝制范围 Sewing range	800x600mm	重量 Weight	330Kg
机针型号 Needle model	Dpx17 11#	外型尺寸 Dimensions	1600x1500x1260mm(LxWxH)
电压 Voltage	单相 Single phase 200-240V		

以上基础参数表为标准款机型