

为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.



舒普智能技术股份有限公司
SUPREME INTELLIGENT TECHNOLOGY CO.,LTD
地址：宁波市鄞州区金源路728号
No.728 JinYuan Rd.Yinzhou District,
Ningbo 315100, China
TEL: 0086-574-88393716 88393738
FAX: 0086-574-88393717
E-mail: china-supreme@vip.163.com
www.china-supreme.com

华北办事处
山东省青岛市流亭街道赵红路 58 号
18858089509 谢春光

郑州办事处
河南省郑州市南三环大学路大学南都一号楼门面房 1-35
18858092819 高得正

晋江办事处
福建省晋江市池店镇新店顶街西路 267 号
18858088922 洪明艺

苏北办事处
江苏省宿迁市沭阳县经济开发区昆山路科创园 1 号厂房
18858085970 彭振庭

苏南办事处
江苏省无锡市锡山区合心路 9-2 号
18858093733 杭义平

东北办事处
辽宁省沈阳市于洪区道义大路 79 号融创融公馆东门门市 12 门
15168137390 谢灵龙

杭州办事处
浙江省杭州市临平区文正街 4 号艺尚创客中心 2 幢 1 楼 108 室
18858089061 何路华

武汉办事处
湖北省武汉市黄陂区盘龙城经济开发区佳海轻纺城宋岗二路 51-55 号
18171150210 蔡志刚

南昌办事处
江西省南昌市青山湖区昌新路 168 号
18858088922 洪明艺

SP-FSMC9513-M

智能模板机
Intelligent Template Machine



性能优势:

采用智能闭环缝制系统,实时监控缝制状态,以反馈交互的方式,调控缝制系统。
采用 RFID 先进芯片识别技术,反应更加快速、灵敏和准确。
采用首创重力式旋梭供油机构,从更根本上,保证供油力恒定,保证供油的稳定性。
采用大行程针杆机构,机针高度达 22mm,在不同厚度的模板或布料的缝制,应用上,适用性更广泛。
采用智能机械压脚,在具备了智能控制系统的灵活性,同时也具备了机械结构稳定性。
采用丝杠传动系统,结合闭环电机,缝制精度达 0.1 毫米级别。
选购功能装置:激光切割、振动刀切割、丝杆模组、自动起缝装置。

效率:

通过电脑控制,缝品线迹稳定标准,花样如出一辙,从根本上改变了缝制工艺,极大的提升了缝制效益和质量。

适用范围:

采用智能闭环控制系统,擅长于缝制花样特别复杂的产品。

Advantages


The intelligent closed-loop sewing system is adopted to monitor sewing operation in real time and to control the sewing operation by means of feedback interaction.
RFID advanced chip identification technology, easy to use, more rapid and accurate response.
Using gravity-type rotary hook oil supply technology, which ensures the constant oil supply and the stability.
Large stroke needle rod mechanism, needle height up to 22mm, enable to use for different thickness of fabrics and for different sewing application.
The intelligent mechanical presser foot has the flexibility of an intelligent control system and the stability of the mechanical structure.
Using screw rod with motor control, sewing accuracy can reach to 0.1 mm.
Optional: laser cutting, vibration knife cutting, double screw rods, automatic sewing function

Efficiency

Through computer control, the stitches of the sewing product are stable to the standard and the pattern is exactly the same, which fundamentally changes the sewing process and greatly improves the sewing efficiency and quality.

Application

It adopts intelligent closed-loop control system and is good at sewing products with particularly complicated patterns.



视频及资料下载
Video and data download

最高缝制速度 Highest sewing speed	3500rpm	气压 Air pressure	0.5Mpa, 1.8L/min
缝制范围 Sewing range	1300×950mm	重量 Weight	265Kg
机针型号 Needle model	DP×17	外型尺寸 Dimensions	2250×2200×1300mm(L×W×H)
电压 Voltage	单相 Single phase200-240V		

以上基础参数表为标准款机型